

The Mechanical Extraction of Lipids via Traditional Wooden Wedge Presses: A Multidisciplinary Analysis of Oilseed and Fruit Processing

Introduction and the Historical Evolution of Mechanical Expression

The mechanical extraction of vegetable oils and fruit lipids represents one of the most mechanically demanding, economically significant, and biochemically complex engineering processes developed prior to the Industrial Revolution. Before the widespread deployment of continuous high-pressure screw expellers, advanced hydraulic presses, and volatile solvent extraction protocols, human societies relied on the generation of immense kinetic and static forces to rupture the highly resistant cellular matrices of oleaginous materials. Archaeological excavations from the Indus Valley Civilization and subsequent historical records from the Roman Empire indicate that early societies utilized primitive crushing systems, such as the mortar-and-pestle *ghani* or the towering stone *trapetum* and *mola olearia*, which relied heavily on animal traction, sheer mass, and the mechanical advantage of the simple lever¹.

However, as the global demand for dietary lipids, industrial lubricants, and illumination fuels expanded exponentially, the limitations of lever-based and weight-based presses became a severe bottleneck. The ultimate pressure output of a traditional lever press is inherently constrained by the tensile limits of its wooden components and the gravitational limits of its stone counterweights¹. The paradigm shifted definitively with the perfection of the wooden wedge press. Emerging in sophisticated forms in China over 1,500 years ago and culminating in the formidable European "Dutch oil mill" (*oliemolen*) of the seventeenth and eighteenth centuries, the wedge press bypassed the limitations of direct mass¹.

By harnessing the kinetic energy of massive wooden stamping poles—often lifted by the rotary power of waterwheels or advanced windmills and dropped repeatedly onto a double-inclined plane—these pre-industrial behemoths successfully converted low-velocity vertical energy into catastrophic horizontal compressive forces¹. The Dutch milling industry, particularly in the Zaan region north of Amsterdam, became one of Europe's earliest large industrial districts. Aided by the 1592 invention of the crankshaft by Cornelis Corneliszoon, which efficiently transformed rotary motion into vertical reciprocating movement, over 1,200 mills operated in the region over its history, with roughly 600 active simultaneously around the year 1700⁶. While early mechanical operations relied on human or animal muscle, a typical Dutch windmill could generate between 14 and 18 horsepower, equivalent to the labor of approximately 150 men, providing the staggering force necessary to execute industrial-scale cellular rupture⁷.

The engineering of a heavy-duty wooden wedge press demands a rigorous synthesis of

classical mechanics, tribology, extraction thermodynamics, and orthotropic material science. This report provides an exhaustive, expert-level analysis of the mechanical extraction of olive oil and sunflower oil using the traditional wedge press. It details the botanical microstructure of the raw materials, the complex non-Newtonian rheological behavior of the resulting pastes, the thermodynamics of fluid expression, the kinematics of the wedge system, the application of terrestrial consolidation theory to seed cake compression, and the structural verification parameters mandated by modern timber engineering standards.

Botanical Microstructure and Extraction Kinetics

The mechanical efficiency of any oil extraction process is fundamentally governed by the biochemical and microstructural state of the organic material being processed. Lipids in plants are not stored in free-flowing pools; rather, they are securely bound within highly evolved intracellular structures protected by rigid, semi-permeable cell walls composed of cellulose microfibrils, hemicellulose, and pectin¹. Understanding the distinct microstructures of oilseeds and oil-bearing fruits is paramount to executing the correct pre-extraction processing sequences.

In hard oilseeds, such as sunflower seeds (*Helianthus annuus* L.), triacylglycerols are stored in the cotyledons within specialized, highly stable intracellular organelles known as oleosomes or lipid bodies⁹. Oleosomes typically measure between 0.5 and 3.0 micrometers in diameter and are encapsulated by a protective phospholipid monolayer embedded with highly specialized structural proteins, predominantly oleosins, caleosins, and steroleosins⁹. The structural biology of oleosins reveals a hydrophobic hairpin domain of approximately 72 residues—consisting of two alpha helices connected via a proline knot—that is firmly inserted into the triacylglycerol core¹⁰. The hydrophilic N-terminal and C-terminal arms extend outward into the aqueous cytosol¹⁰. This unique molecular architecture provides immense steric and electrostatic stabilization, preventing the internal oil droplets from coalescing even under conditions of extreme environmental desiccation, a survival mechanism for orthodox seeds⁹.

Conversely, the lipids within olive fruits (*Olea europaea*) are primarily synthesized and stored in the fleshy mesocarp tissue³. While developing olive cells also utilize oleosomes, as the fruit matures, these organelles progressively fuse to form a much larger, dominant vacuole known as a lipovacuole, which can ultimately occupy the vast majority of the cellular volume³. The mesocarp cells themselves possess a high moisture content and are suspended within a complex matrix of pectic substances and cellulose microfibrils¹⁴. Recent microstructural analyses indicate the presence of "biomechanical hotspots," which are highly resilient sites of close interaction between cellulose microfibrils mediated by xyloglucans and pectins, giving the fruit its structural integrity¹⁵.

Because of these distinct microstructures, sunflower seeds and olive fruits require fundamentally different sequences of mechanical and thermal pretreatment before they can be effectively processed in a wedge mechanism. The primary objective in both scenarios is to systematically degrade the cellular architecture, dismantle the specific oleosin or pectic barriers, and lower the viscosity of the lipid fraction to facilitate subsequent fluid flow through the tortuous pathways of the compressed matrix¹.

Thermomechanical Pretreatment of Sunflower Seeds

To achieve an optimal extraction yield from hard oilseeds like sunflower, the raw kernels must undergo severe physical size reduction and precise thermal conditioning to overcome the robust stabilization of the oleosomes and the surrounding cellular matrix.

The initial preparatory phase involves the careful cleaning and grading of the raw sunflower seeds to remove chaff, agricultural debris, and stones that could damage the pressing equipment or absorb valuable expressed oil¹. Following this, the seeds are typically dehulled to increase the relative protein content of the residual meal and decrease the abrasive wear on the processing equipment¹⁶. The dehulled seeds are subsequently subjected to mechanical cracking and flaking¹⁶. Using heavy, specialized roller mills, the seeds are sheared and compressed into thin flakes, with an optimal target thickness in the range of 0.25 to 0.37 millimeters¹⁷. This profound physical size reduction drastically increases the surface area-to-volume ratio of the material and initiates the primary physical tearing of the parenchymal cell walls¹. However, mechanical flaking alone is grossly insufficient to release the full lipid payload due to the resilient oleosin proteins guarding the triacylglycerols at the sub-micron level⁹.

Consequently, the flaked sunflower seeds must be subjected to intense thermal conditioning, typically through roasting over a firebox or inside steam-jacketed heating vessels¹. This application of thermal energy accomplishes several vital rheological and structural objectives. Primarily, the heat permanently denatures the structural proteins—including the critical oleosins surrounding the oleosomes as well as the cellular structural proteins within the cell walls¹. This rapid denaturation transforms the previously pliable and sterically stabilized cellular matrix into a highly brittle, degraded structure that readily shatters and yields under the subsequent compressive strain of the wedge press¹.

Simultaneously, the heating process tightly controls the thermodynamic state of the internal moisture. Raw oilseeds contain varying levels of water, which acts as a plasticizer¹⁹. If the moisture content is too high, the water acts as an incompressible fluid cushion within the press, absorbing the immense kinetic energy of the wedge stamper without contributing to cellular rupture, thereby dramatically lowering the final oil yield¹. Alternatively, controlled heating to temperatures between 85°C and 100°C gently vaporizes trace intracellular moisture, creating internal pneumatic pressure that further ruptures the cell walls from the inside out¹. Through this thermomechanical sequence, the final moisture content of the conditioned sunflower flakes is carefully titrated to approximately 8% to 10%, preparing the matrix for expression²⁰.

Pretreatment of Olives: Rheology and Malaxation

Unlike dry sunflower seeds, fresh olives contain a massive aqueous fraction—known as vegetation water—alongside their oil content. The goal of olive pretreatment is not desiccation, but rather the controlled coalescence of the lipid fraction within a highly hydrated, complex non-Newtonian paste.

Traditional milling operations utilize towering cylindrical or conical granite millstones rotating within a fixed stone basin to crush the whole olives¹. These massive stones are meticulously

calibrated to crush the fleshy mesocarp while simultaneously grinding the hard inner pit (the endocarp) into a coarse grit¹³. The endocarp undergoes distinct developmental periods, with massive sclerification and maximum hardening occurring during its growth phases²². The inclusion of the pulverized endocarp in the resulting paste is not an accident of primitive machinery; it is an absolute structural necessity. The sharp, rigid fragments of the pit act as an abrasive medium that physically tears open surviving lipovacuoles during the mixing phase. Later, within the extreme compression of the wedge press, the incompressible endocarp particles act as a vital porous scaffolding, creating microscopic drainage macropores that prevent the complete sealing of the matrix and allow the expressed oil and vegetation water to percolate outward through the dense, fibrous paste¹³.

Once crushed, the olive paste must be continuously and slowly stirred in a crucial conditioning process known as malaxation¹³. This gentle mechanical kneading, typically lasting 30 to 45 minutes, is designed to break the transient water-oil emulsions that formed during the violent crushing phase. The slow agitation allows the microscopic lipid droplets to collide and agglomerate into larger, continuous drops that are significantly easier to separate under static mechanical pressure².

The behavior of the olive paste during malaxation and subsequent pressing is governed by highly complex non-Newtonian fluid mechanics. Rigorous rheological analyses demonstrate that olive paste acts unequivocally as a shear-thinning (pseudoplastic) fluid²³. At rest or under low shear, the complex matrix of hydrated pectins, dispersed cellulose microfibrils, and trapped oil droplets forms a highly entangled, viscoelastic network that heavily resists flow, providing Pickering-like stabilization⁸. However, as the shear rate increases—such as when the paste is driven by the internal movement of the press—the polymeric chains align in the direction of the flow, the agglomerated structures break down, and the apparent viscosity of the paste drops exponentially²⁶.

This behavior is mathematically defined by several advanced rheological models. The most commonly applied is the Power-law model (the Ostwald–de Waele relationship), expressed as:

$$\tau = K\dot{\gamma}^n$$

Where τ represents the shear stress, $\dot{\gamma}$ is the shear strain rate, K is the flow consistency index (indicating the overall baseline viscosity or thickness of the paste), and n is the dimensionless flow behavior index²⁶. For olive paste, the flow behavior index (n) is strictly documented at values less than 1.0, confirming its shear-thinning nature²⁵.

In cases where the paste exhibits a distinct yield stress that must be mechanically overcome before any fluid flow occurs, the Herschel-Bulkley model is more appropriate:

$$\tau = \tau_y + K\dot{\gamma}^n$$

Where τ_y represents the yield stress³¹. To capture the entire rheological profile, including extreme shear rates, engineers utilize the Bird-Carreau or Cross-Power models, which incorporate bounds for viscosity at zero shear (ν_0) and infinite shear (ν_∞)²⁵. The Cross-Power law is formulated as:

$$\nu = \nu_\infty + \frac{\nu_0 - \nu_\infty}{1 + (m \cdot \dot{\gamma})^n}$$

Where m represents the natural time constant at which linear behavior transitions to the power law²⁵. Variations in the maturity of the olive drupes, the specific geometry of the crushing machinery, and the addition of trace water during malaxation heavily dictate the consistency index and yield stress parameters, directly dictating how successfully the non-Newtonian paste will yield under the static pressures applied by the wedges²³.

Thermodynamics of Fluid Expression: The Andrade Equation

A core physical principle bridging the extraction of both sunflower seed oil and olive oil is the absolute necessity of minimizing the dynamic viscosity of the target lipid prior to pressing. According to the foundational principles of fluid mechanics, the viscosity of vegetable oils is highly temperature-dependent, decreasing exponentially as the ambient thermal energy increases¹. This inverse relationship occurs because elevated temperatures provide the complex lipid molecules with sufficient kinetic energy to overcome the intermolecular attractive forces (van der Waals forces) binding them together, thereby radically reducing internal fluid friction and allowing the lipid to flow freely³⁴.

The specific temperature-viscosity dependency of these complex hydrocarbon mixtures is most accurately modeled by the Andrade equation, which serves as a viscosity analogue to the Arrhenius activation energy law³⁶. The classic two-parameter Andrade model is expressed as:

$$\ln(\eta) = A + \frac{B}{T}$$

Where η is the dynamic viscosity (typically measured in Pascal-seconds or centipoise), T is

the absolute temperature in Kelvin, A is the pre-exponential constant (representing the theoretical high-temperature limiting viscosity or infinite-temperature viscosity), and B is a flow-activation term³⁶. The term B is directly related to the activation energy required for viscous flow (E_a) via the ideal gas constant (R), calculated as $E_a = R \cdot B$ ³⁶. Empirical testing across various vegetable oils confirms distinct rheological profiles based on lipid composition.

Oil Type	Parameter A	Parameter B (K)	Activation Energy (Ea)	Correlation (R2)
Sunflower Oil	-	-	Lower relative E_a	> 0.99
Olive Oil	-	-	Highest relative E_a	> 0.99
Avocado Oil	Highest ν_∞	-	-	> 0.99

(Data representing general trends extracted from comparative kinetic viscosity studies modeling the Arrhenius relationship³⁵)

Analyses demonstrate that olive oil, characterized by a massive concentration of monounsaturated fatty acids (specifically oleic acid), possesses a higher baseline dynamic viscosity and a significantly larger activation energy (E_a) than sunflower oil, which is heavily dominated by polyunsaturated linoleic acid³⁵. Because of this inherently high viscosity, forcing cold oil through the tortuous, microscopic capillary network of compressed fibrous seed cake or dense olive paste requires immense and sustained pressure¹. To optimize commercial yield, modern and historical pressing operations purposefully elevate the temperature of the seed mass. Hot-pressing sunflower seeds at high temperatures (110°C to 140°C) radically decreases the dynamic viscosity, allowing the oil to flow rapidly and efficiently from the solid matrix¹. However, this thermodynamic manipulation involves a strict and uncompromising biochemical trade-off. While high heat maximizes the volumetric yield by minimizing viscosity, it initiates rapid lipid autoxidation, encourages the Maillard reaction, and severely degrades heat-sensitive polyphenols, antioxidants, and fat-soluble vitamins¹. Consequently, "cold-pressing" is legally and technically defined by maintaining the processing temperature strictly below 27°C for olives, or 40°C to 45°C for seed oils¹. Cold extraction

perfectly preserves the organoleptic and biochemical integrity of the extra-virgin product, but the exponentially higher viscosity of the cold oil fiercely resists expression, leaving a significant percentage of the valuable lipid payload permanently trapped within the residual pomace¹.

Filtration Matrices, Microbiological Hazards, and Sensory Integrity

Once the raw material is thermally and mechanically conditioned, it must be loaded into the wedge press. Because the internal pressures generated by the kinetic wedge strikes are catastrophic, the pulverized seed cake or semi-liquid olive paste cannot simply be poured into the wooden trough; it must be completely enclosed within an ultra-high-pressure filtration membrane¹.

Historically, this critical function was achieved using heavy, circular woven mats. For olive processing, these distinct mats are known regionally as *scourtins* (in France) or *fiscoli* (in Italy)². Originally hand-woven from tough, coarse natural fibers such as esparto grass, hemp, or thick coconut fiber, these central-hole envelopes are manually stuffed with layers of olive paste and stacked vertically³. For dry oilseeds like sunflower, linseed, or hemp, the hot, crushed seeds are tightly packed into woven woolen or canvas bags, which are subsequently wrapped in thick, leather-backed horsehair mats to provide extreme tensile reinforcement¹.

This composite wrapping serves two conflicting but essential mechanical purposes: it must possess sufficient structural tensile strength to prevent the highly pressurized solid paste from violently extruding or blowing out under load, while simultaneously maintaining sufficient weave porosity to allow the low-viscosity oil and vegetation water to percolate outward¹.

While mechanically brilliant for containment, the reliance on natural fiber *scourtins* and *fiscoli* represents the single greatest vulnerability of the traditional wedge press regarding final product quality and food safety. Natural plant and animal fibers are inherently highly absorbent. During the lengthy extraction cycles, the fibers become permanently saturated with lipid fractions, cellular vegetation water, and microscopic fragments of fruit or seed pulp⁴⁶. Between pressing batches, these trapped organic remnants undergo rapid, uncontrolled enzymatic degradation and microbial spoilage within the porous weave³.

When fresh, high-quality paste is pressed through these contaminated mats, the resulting oil is instantly inoculated with spoilage bacteria (such as *Clostridium* or *Pseudomonas*), yeasts, and fungi⁴⁷. This phenomenon is the direct origin of the most notorious sensory defects strictly monitored and defined by modern European Union olive oil marketing standards, specifically Commission Delegated Regulation (EU) 2022/2104 and Implementing Regulation (EU) 2022/2105⁴⁸. These regulations mandate rigorous organoleptic conformity checks where trained tasting panels screen for specific microbiologically induced defects:

- **Fusty / Muddy Sediment:** A profound defect characterized by a swampy, fermented odor. This occurs when the oil is extracted from paste that has undergone advanced anaerobic fermentation within the contaminated mats or when oil is left in prolonged contact with the sediment at the bottom of traditional collection vats⁵¹.
- **Musty-Humid-Earthy:** A moldy flavor indicating that the extraction mats or the stored

olives were heavily colonized by yeasts and fungi due to excessive humidity⁵².

- **Rancidity:** A stale, putrid flavor caused by the advanced autoxidation of the residual lipids trapped in the mats from previous batches⁴⁷.

To circumvent these severe microbiological limitations while maintaining the mechanical mechanics of the press, modern artisanal producers have completely abandoned esparto grass and coconut fibers. They have replaced them with synthetic, food-grade polypropylene or nylon *scourtins*³. These synthetic variants provide identical tensile strength and precise filtration but possess a closed-cell physical structure that can be aggressively sterilized, preventing anaerobic fermentation and successfully preserving the virgin chemical profile of the oil⁴⁵.

The environmental impact of the residual waste also heavily distinguishes traditional pressing from modern extraction. Traditional pressing yields a relatively dry solid pomace (25% to 30% moisture)⁵⁸. Modern continuous two-phase centrifugal decanters, while vastly superior in hygiene and labor efficiency, produce a highly polluting, semi-liquid sludge known as *alperujo*, which contains 55% to 70% water and poses severe ecological disposal challenges⁵⁸. Thus, traditional pressing, if utilizing synthetic mats, presents a significantly lower environmental footprint regarding wastewater generation.

Architectural Geometry and Classical Mechanics of the Wedge System

The structural and mechanical core of the operation is the wooden wedge press itself, a marvel of applied physics scaled to massive proportions during the zenith of the Dutch milling era. The foundational backbone of the press is a monolithic timber component known as the main beam or base log. Historical blueprints dictate the use of massive logs measuring over nine feet in length and twenty-seven inches square in cross-section¹. Mortised directly into the longitudinal center of this main beam is a deep, precise rectangular cavity known as the trough. The vertical end-grain shoulders of this mortise serve as the ultimate, immovable abutments against which the entire compressive force of the kinematic system is directed¹.

The seed packets, secured within their protective mats, are positioned at the extreme ends of the trough, bearing directly against the mortise shoulders¹. To maintain the elevated temperature of the pre-roasted sunflower seed cake—actively combating the thermodynamic rise in lipid viscosity—heavy iron plates, pre-heated in dedicated furnaces, are inserted immediately adjacent to the seed packets¹. The remaining central void of the trough is subsequently packed with solid, end-grain hardwood spacer blocks and the active kinematic mechanisms: a downward-pointing primary pressing wedge (the driving wedge) and an inverted releasing wedge¹.

The operational cycle relies on the direct conversion of vertical kinetic energy into horizontal static strain. Heavy wooden stamping poles, suspended vertically above the press, are utilized as kinetic projectiles. The mill mechanism—a massive cam rotating on a wind- or water-driven main shaft—repeatedly raises the primary stamping pole and allows it to free-fall onto the broad upper face of the pressing wedge¹.

The total vertical energy delivered to the top of the wedge is dictated by the classical law of conservation of energy:

$$E_k = m \cdot g \cdot h$$

Where E_k is the kinetic energy at the exact moment of impact, m is the mass of the stamper in kilograms, g is gravitational acceleration (9.81 m/s^2), and h is the drop height in meters¹. For an industrial-scale press utilizing a 150-kilogram oak stamper dropped from a height of 1.2 meters, the kinetic energy generated per single strike is approximately 1,765 Joules¹.

Upon striking the wedge, the work-energy theorem dictates the transient vertical driving force:

$$F_{avg} = \frac{E_k}{d}$$

Where d is the microscopic downward displacement of the wedge per strike. As the highly compressed seed cake reaches its terminal density, the system becomes highly inelastic, and d shrinks to fractions of a millimeter. Consequently, the instantaneous average vertical force (F_{avg}) spikes exponentially, translating the 1,765 Joules of kinetic energy into hundreds of kilonewtons of downward driving force¹.

Statics, Tribology, and the Self-Locking Wedge Condition

This massive vertical force (P) must be successfully redirected laterally (W) to crush the seed cake against the mortise shoulders. The wedge acts as a mobile, double-inclined plane, providing an immense theoretical mechanical multiplier. However, the theoretical mechanical advantage is entirely dominated by the tribological reality of dry friction between the heavily loaded, sliding wooden faces¹.

Assuming a symmetrical wedge with a half-angle α and a uniform coefficient of static friction μ_s across all interacting wooden surfaces, the lateral output force is governed by the simultaneous static equilibrium equation derived from the resolution of normal and frictional vectors:

$$P = W \left[\frac{2\mu_s \cos \alpha + (1 - \mu_s^2) \sin \alpha}{\cos \alpha - 2\mu_s \sin \alpha} \right]$$

This relationship mathematically reveals that to maximize the lateral crushing force W for any given stamper impact P , the press engineer must utilize the narrowest possible wedge angle α ¹. However, narrowing the angle introduces the single most critical and dangerous failure mode in wedge press engineering: the loss of the self-locking condition. When the stamper is lifted by the cam to prepare for the subsequent blow, the vertical driving force P instantaneously drops to zero. The hyper-compressed seed cake, acting as a massive mechanical spring, exerts violent, reactive lateral pressure against the spacer blocks, attempting to squeeze the driving wedge upward and violently eject it from the trough¹. The only physical force preventing this catastrophic, potentially lethal kinetic ejection is static friction.

For the press to function safely, it must be inherently "self-locking." This condition dictates that the angle of friction (ϕ), which is the arctangent of the coefficient of static friction ($\phi = \tan^{-1}(\mu_s)$), must strictly exceed the geometric half-angle of the wedge ($\alpha < \phi$)¹. In dry structural timber (for example, oak sliding on oak parallel to the grain), the static friction coefficient is highly resistive ($\mu_s \approx 0.62$), yielding a highly safe dry friction angle of roughly 31.8 degrees¹.

However, the oil press presents a fundamentally altered tribological environment. As the cellular membranes of the seeds rupture during pressing, the expressed lipids perpetually saturate every internal wooden surface. Vegetable oils act as highly efficient boundary lubricants, dropping the static friction coefficient of the impregnated wood catastrophically to a range of 0.35 to 0.39¹.

Under these perpetually lubricated conditions, the friction angle plummets:

$$\phi_{lubricated} = \tan^{-1}(0.35) \approx 19.2^\circ$$

Consequently, to ensure absolute, fail-safe self-locking functionality, the wedge half-angle (α) must never exceed 19 degrees¹. To provide a rigorous engineering margin of safety against the dynamic shockwaves and intense vibrations induced by the heavy stamping poles, historical and modern wedges are precisely planed to highly acute half-angles restricted to 10 to 12

degrees (resulting in a total wedge taper of 20 to 24 degrees)¹. This strict geometric constraint ensures safety but inherently requires the use of exceptionally long wedges to achieve the necessary total lateral displacement.

Terzaghi's Consolidation Theory and Poroelasticity

As the wedge drives laterally outward, it subjects the seed cake to profound physical consolidation. The extraction of oil from a solid matrix under intense stress does not occur instantaneously; it is governed by the complex interplay of solid matrix deformation and fluid expulsion over prolonged periods. This dynamic process is mathematically characterized by adapting Terzaghi's one-dimensional consolidation theory—originally developed in geotechnical engineering to describe the gradual settlement of saturated clay soils under structural foundation loads—to the biomechanics of agricultural oilseeds⁶².

Biot's subsequent theory of poroelasticity expanded upon Terzaghi's foundation, establishing a rigorous continuum model for fully saturated porous materials consisting of a solid skeleton and an interconnected pore fluid⁶⁵. Bargale's foundational application of these theories to mechanical oil expression demonstrates that the seed cake acts precisely as a saturated porous medium once the initial compaction expels trapped atmospheric air and the ruptured cellular oil floods the inter-kernel voids⁶⁴.

The flow of the highly viscous lipid through these microscopic, interconnected voids is described by Darcy's Law:

$$q = -\frac{k}{\gamma_w} \frac{\partial u}{\partial z}$$

Where q is the fluid flow flux, k is the coefficient of permeability, γ_w represents fluid density parameters, and $\partial u / \partial z$ is the hydraulic gradient (the profound pressure difference forcing the oil through the matrix)⁶³.

In Terzaghi's paradigm, the total applied stress (σ) generated by the mechanical wedge is partitioned into effective stress (σ' , borne exclusively by the fibrous, solid skeleton of the seed cake) and pore fluid pressure (u , borne by the initially incompressible vegetable oil)⁶³. The fundamental partial differential equation governing the dissipation of the oil pressure over time (t) and depth (z) is defined as:

$$\frac{\partial u}{\partial t} = C_v \frac{\partial^2 u}{\partial z^2}$$

Where C_v is the critical coefficient of consolidation⁶³. Bargale's mathematical model solves this consolidation equation for two specific loading regimes experienced in the wedge press: a linearly increasing load (as the stamper actively strikes the wedge) and a constant load (during the dwell time between strikes)⁶⁴.

For the constant load phase, the volume of oil expressed (Q) is derived as:

$$Q = K_1[1 - \exp(-K_2t)]$$

Where K_1 and K_2 are complex constants heavily dependent on the specific compressibility of the seed kernel, the average surface area of the voids, and the coefficient of permeability⁶⁴. The consolidation curve representing this extraction demonstrates a distinct inflection point, which engineers utilize to mathematically determine the exact coefficient of consolidation for various seed types⁷⁰.

Crucially, as the oil slowly escapes the matrix, the void ratio (e) of the seed cake drastically decreases, resulting in the exponential densification of the solid material. Consequently, the coefficient of permeability (k) is not a static variable; it decreases continuously as the physical pathways for fluid escape are squeezed shut by the rising effective stress on the solid skeleton⁶³. This poroelastic reality strictly dictates the operational rhythm of the wedge press: the human operator must leave the wedge in its fully locked, highly stressed position for several minutes (the "dwell time") to allow the slow, viscous diffusion of the lipids to reach equilibrium before applying subsequent kinetic strikes¹.

Structural Timber Engineering and Fracture Mechanics (Eurocode 5)

The immense, sustained lateral pressure gradients required to drive Terzaghi consolidation—routinely exceeding 15 Megapascals (MPa) of internal pressure to achieve successful fluid expression—place the timber body of the press under extreme structural duress¹. Wood is a profoundly orthotropic material, meaning its mechanical properties differ drastically along three mutually perpendicular axes: the longitudinal axis (parallel to the grain), the radial axis, and the tangential axis (perpendicular to the grain)¹. To guarantee the physical survivability of the press, its geometry and material selection must be rigorously verified

against the advanced protocols of modern timber engineering, specifically the European standard Eurocode 5 (EN 1995-1-1)¹.

Compression Perpendicular to the Grain Verification

The primary and most frequent mode of catastrophic failure in a heavy-duty wooden wedge press is localized crushing perpendicular to the grain. As the wedge descends, it drives the solid spacer blocks laterally into the vertical, end-grain shoulders of the mortised trough. When timber is subjected to intense perpendicular compression, the microscopic, tubular cellulose structures—primarily the tracheids and vessels—undergo severe plastic buckling and complete structural collapse¹.

Eurocode 5 strictly governs this failure mode, dictating that the design compressive stress ($\sigma_{c,90,d}$) must not exceed the timber's design compressive strength ($f_{c,90,d}$), modified by a highly critical enhancement factor known as $k_{c,90}$ ¹:

$$\sigma_{c,90,d} \leq k_{c,90} \cdot f_{c,90,d}$$

The $k_{c,90}$ parameter is introduced to account for the specific load configuration, the geometric risk of splitting, and the degree of acceptable compressive deformation¹. Because the localized lateral force from the spacer blocks is exerted against a continuous inner beam face, the highly stressed timber fibers directly beneath the blocks are flanked by unstressed, continuous fibers extending along the remainder of the massive beam. These adjacent fibers act as tension members, generating a reinforcing phenomenon known structurally as the "rope effect," which can be mathematically modeled using the Boussinesq solution for stresses under a foundation¹. This mechanically increases the effective load-bearing area, permitting a $k_{c,90}$ multiplier greater than 1.0 (typically up to 1.5 or 1.75 for continuous supports)¹.

However, even with this mathematical enhancement, standard construction softwoods (such as structural pine or spruce) possess characteristic compressive strengths ($f_{c,90,k}$) of only 2.0 to 2.7 MPa¹. Subjecting softwoods to the 15+ MPa required for lipid extraction results in instantaneous, catastrophic crushing of the mortise shoulders¹. Therefore, the utilization of ultra-high-density hardwood is an absolute structural necessity.

Shear Capacity and Mode I Fracture Mechanics

Beyond localized crushing, the outward lateral expansion of the wedge places the entire length of the main beam under extreme longitudinal shear stress. The deep mortised trough acts structurally as a massive notch in the absolute center of the beam. According to linear elastic fracture mechanics embedded within Eurocode 5 (Equation 6.60), abrupt geometric notches induce severe, localized stress concentrations at their internal corners¹.

These sharp corners serve as the focal points for rapid Mode I crack propagation and

devastating cleavage failures along the longitudinal grain lines¹. Eurocode 5 dictates that the induced design shear stress (τ_d) must remain strictly below the timber's design shear strength ($f_{v,d}$), modified heavily by the notch reduction factor (k_v) to penalize the geometry¹:

$$\tau_d \leq k_v \cdot f_{v,d}$$

The reduction factor k_v is calculated based on the notch position, slope, and effective depth (h_{ef}), reflecting the fact that the resistance against crack growth is heavily dependent on the energy release rate threshold required to propagate a fracture through the anisotropic cellular structure¹. To counter these immense splitting forces, historical Dutch millwrights intentionally left massive excess timber extending far behind the mortise trough and frequently bound the outer dimensions of the beam in heavy, shrink-fitted wrought-iron hoops¹. These metal hoops provided active structural confinement, drastically increasing the timber's resistance to tension perpendicular to the grain¹.

Metallurgical-Equivalent Hardwood Selection and Impregnation Dynamics

To satisfy the extreme, concurrent demands of parallel compressive strength (for the wedges and stampers), perpendicular compressive strength (for the trough shoulders), longitudinal shear capacity, and cyclic impact resistance, the meticulous selection of the hardwood species is the paramount engineering decision¹.

Based on Eurocode 5 strength classifications (EN 338), three primary deciduous species are typically evaluated for such extreme industrial applications: White Oak (*Quercus petraea*), European Beech (*Fagus sylvatica*), and European Hornbeam (*Carpinus betulus*)¹.

Structural Property / Parameter	White Oak (<i>Quercus petraea</i>)	European Beech (<i>Fagus sylvatica</i>)	European Hornbeam (<i>Carpinus betulus</i>)
Density (Air Dry, ρ_k)	0.67 - 0.75 g/cm ³	0.70 - 0.74 g/cm ³	0.74 - 0.83 g/cm ³
Compressive Strength Parallel ($f_{c,0,k}$)	54 - 66 MPa	55 - 62 MPa	68 - 85 MPa

Compressive Strength Perpendicular ($f_{c,90,k}$)	$\approx$ 10 - 11 MPa	$\approx$ 10 - 12 MPa	$\approx$ 13 - 15 MPa
Brinell Hardness (Perpendicular)	26 - 31 N/mm ²	34 - 38 N/mm ²	33 - 45 N/mm ²
Impact Bending Strength	60 - 70 kJ/m ²	78 - 82 kJ/m ²	60 - 89 kJ/m ²
Shear Strength Parallel ($f_{v,k}$)	11 - 13 MPa	12 - 14 MPa	14 - 16 MPa

(Data derived from standardized 12% to 15% equilibrium moisture content parameters¹)

An analysis of the mechanical matrices reveals that European Hornbeam is the unequivocal, optimal selection for the fabrication of the wedge press. Hornbeam possesses the highest density of native European diffuse-porous hardwoods, routinely exceeding 0.76 g/cm³ and

reaching 0.83 g/cm³¹. Its towering $f_{c,90,k}$ value (up to 15 MPa) guarantees that the mortise shoulders can absorb the extreme, localized crushing forces generated by the laterally expanding wedges without plastically yielding¹.

Crucially, Hornbeam is characterized by a complex, interlocked, and deeply integrated cellulose grain structure¹. Unlike straight-grained woods, this structural anomaly provides extraordinarily

high fracture toughness and shear strength ($f_{v,k}$ of 14 to 16 MPa), making it remarkably resistant to the stress concentrations and catastrophic splitting forces induced at the mortise notch¹.

Furthermore, the continuous pounding of the heavy 150 kg stampers introduces profound low-cycle impact fatigue, which generally causes the localized kinking of cellulose microfibrils and ultimate broom-like splintering of timber components¹. Hornbeam's supreme impact bending strength (up to 89 kJ/m²) allows its cellular matrix to repeatedly absorb violent kinetic energy without suffering rapid brittle fracture¹. Its elite Brinell surface hardness (peaking at 45 N/mm²) ensures that the highly acute, strictly calculated 10-degree faces of the pressing wedges do not plastically deform or "mushroom" under repetitive strikes, permanently preserving the critical self-locking tribological geometry required to prevent ejection¹.

High-grade Hornbeam readily satisfies the requirements for the elite D60 or D70 Eurocode 5 strength classes, earning it the historical moniker of "ironwood" among traditional millwrights¹.

A final, highly nuanced dynamic in the long-term operation of the wooden press is the deep internal impregnation of the Hornbeam timber by the extracted oils. While this saturation drops the static friction coefficient—necessitating the acute wedge angles—it provides profound physiochemical enhancements¹. The dense, hydrophobic lipid molecules physically occlude the cellular pits and coat the highly reactive hydroxyl groups within the cellulose matrix, establishing a permanent hydrophobic barrier¹. This radically improves the dimensional stability of the press, reducing swelling and shrinkage coefficients by up to 33% and actively preventing the development of microscopic shrinkage checks (cracks) that would otherwise serve as fatal stress risers¹. Furthermore, the viscoelastic nature of the oil-saturated cellular matrix acts as an internal acoustic shock absorber, dampening the high-frequency vibrational transmission from the stamper impacts and actively protecting the main beam from long-term acoustic fatigue¹. Finally, the constant presence of the incompressible hydrodynamic film provides boundary lubrication between the sliding wedge faces, virtually eliminating abrasive wear and galling, thus preserving the precise geometry of the apparatus over thousands of pressing cycles¹.

Conclusion

The traditional wooden wedge press stands as a masterclass in pre-industrial mechanical engineering, brilliantly leveraging the static mechanical advantage of the double-inclined plane to entirely bypass the limitations of muscle and gravity. The successful extraction of lipids from heavily guarded botanical structures—whether the sterically stabilized oleosomes of the low-moisture sunflower seed or the pectic-bound lipovacuoles of the highly shear-thinning olive paste—requires the precise manipulation of thermal chemistry, cellular rupture, and extreme compressive stress.

The fluid mechanics of the process strictly dictate the necessity of elevated temperatures to exponentially lower lipid viscosity according to the Andrade equation, while the application of Terzaghi's consolidation theory and Biot's poroelasticity illustrates the absolute necessity of prolonged dwell times to force the highly viscous fluids through the densifying porous matrix of the seed cake. To successfully translate vertical kinetic impacts into the sustained horizontal forces required for this consolidation, the press relies on a highly critical tribological balance. In a constantly oil-saturated environment, boundary lubrication forces the wedge half-angle to remain strictly below 19 degrees—practically engineered at 10 to 12 degrees—to maintain a fail-safe, self-locking state against the reactive elasticity of the compressed seed cake. These immense lateral forces generate severe stress concentrations, pushing the very limits of orthotropic material science. Verified against the strict structural fracture mechanics and limit state protocols of Eurocode 5 regarding compression perpendicular to the grain and longitudinal shear capacity, standard construction timbers fail catastrophically. The architecture exclusively demands elite, ultra-high-density hardwoods, with European Hornbeam emerging as the definitive metallurgical equivalent due to its interlocked grain, exceptional fracture toughness, and supreme resistance to cyclic impact fatigue. Ultimately, the successful synthesis of fluid thermodynamics, non-Newtonian rheology, wedge statics, and advanced timber mechanics allows the traditional wedge press to achieve modern industrial extraction pressures entirely through organic materials and kinetic ingenuity.

Works cited

1. 15 - Wooden Wedge Oil Press Design.pdf
2. What Is an Olive Press? History, How It Works, and the Modern Mill,
<https://exauoliveoil.com/blogs/olive-oil/what-is-an-olive-press>
3. Olive oil extraction - Wikipedia, https://en.wikipedia.org/wiki/Olive_oil_extraction
4. Horse-driven oil mill - Nederlands Openluchtmuseum,
<https://www.openluchtmuseum.nl/en/locaties/ros-oliemolen>
5. In-Depth Articles - Technology of the Oil Mill Industries,
https://www.engr.psu.edu/mtah/articles/technology_oilmill.htm
6. Windmills and Historic Milling Traditions of the Netherlands,
<https://statiqly.com/windmills-and-historic-milling-traditions-of-the-netherlands/>
7. Dutch Windmills Left Behind | The Inconsequential Diary,
<https://theinconsequentialdiary.wordpress.com/2020/06/16/dutch-windmills-left-behind/>
8. Unravelling the Mechanism of Stabilization and Microstructure of Oil,
<https://doi.org/10.1021/acsabm.8b00385>
9. Natural Oleosomes from Nuts and Seeds: Structural Function ... - MDPI,
<https://www.mdpi.com/1999-4923/18/2/144>
10. The role of oleosins and phosphatidylcholines on the ... - WUR eDepot,
<https://edepot.wur.nl/674257>
11. An insight on their microstructure - maize germ vs sunflower seed,
<https://research.wur.nl/en/publications/oil-bodies-an-insight-on-their-microstructure-maize-germ-vs-sunfl/>
12. Leading Edge Technologies and Perspectives in Industrial Oilseed,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC10459726/>
13. Production methods - European Olive Oil,
<https://oliveoileu.jp/en/production-methods.html>
14. Implication for structural and mechanical properties of cell wall,
https://www.researchgate.net/publication/230575325_Properties_of_cellulosepectins_composites_Implication_for_structural_and_mechanical_properties_of_cell_wall
15. Microstructural and Texturizing Properties of Partially Pectin ... - MDPI,
<https://www.mdpi.com/2304-8158/10/11/2644>
16. Oilseeds preparation & pressing - Desmet,
<https://www.desmet.com/en/feed/oilseeds-preparation-pressing>
17. Essential Unit Operations for Oil Extraction from Oilseeds,
<https://agriculture.institute/pulses-oilseeds-processing/essential-unit-operations-oil-extraction-oilseeds/>
18. Intangible Heritage of the Netherlands - Oliemolens.nl - Olieslaan,
<https://olieslaan.nl/en/home-english/>
19. New approach for the elucidation of the phenomena involved in the,
https://www.ocl-journal.org/articles/ocl/full_html/2022/01/ocl210052/ocl210052.html
20. Tips & Tricks – Pretreatment in Sunflower Oil Production Process,

<https://www.abcmach.com/oil-pressing/sunflower-oil-production-process-pretreatment-tips.html>

21. The milling of olives – Elaisian,
<https://www.elaisian.com/en/2022/06/13/milling-of-olives/>
22. Endocarp Development Study in Full Irrigated Olive Orchards ... - MDPI,
<https://www.mdpi.com/2223-7747/11/24/3541>
23. Modelling the Rheology of Olive Paste for Oil Extraction Plant ... - PMC,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC10253159/>
24. Olive Oil Extraction Process - Growables,
<https://www.growables.org/information/TropicalFruit/OliveExtraction.htm>
25. Non-Newtonian Models | Materials - SimScale,
<https://www.simscale.com/docs/simulation-setup/materials/non-newtonian-models/>
26. Power-law fluid - Wikipedia, https://en.wikipedia.org/wiki/Power-law_fluid
27. Mustansiriyah University College of Engineering Materials,
https://uomustansiriyah.edu.iq/media/lectures/5/5_2020_10_06!07_49_49_AM.pdf
28. Non-Newtonian Fluids: Unveiling the Fascinating World of Flowing,
<https://www.fishersci.se/se/sv/lab-reporter/2023/issue-4/non-newtonian-fluids.html>
29. Quantifying Shear Thinning Behavior on a Rotational Rheometer,
<https://analyzing-testing.netzsch.com/en/application-literature/quantifying-shear-thinning-behavior-on-a-rotational-rheometer-using-the-power-law-model>
30. assessment of the viscosity value in olive oil paste using different,
<https://www.cabidigitallibrary.org/doi/pdf/10.5555/20093272800>
31. Herschel-Bulkley Model - Documentation,
<https://docs.aft.com/impulse/Herschel-Bulkley-Model.htm>
32. Non-Newtonian Viscosity Models - Fluid Flow Help Center,
<https://knowledge.fluidflowinfo.com/en/articles/13271434-non-newtonian-viscosity-models>
33. Combined Continuous Machine to Condition Olive Paste,
<https://www.cetjournal.it/cet/21/87/048.pdf>
34. Temperature dependence of viscosity - Wikipedia,
https://en.wikipedia.org/wiki/Temperature_dependence_of_viscosity
35. (PDF) Comparison of selected vegetable oils rheologic properties,
https://www.researchgate.net/publication/320640187_Comparison_of_selected_vegetable_oils_rheologic_properties
36. Andrade Equation Calculator | MetricGate,
<https://metricgate.com/docs/andrade-viscosity-equation/>
37. Temperature dependence of density and viscosity of vegetable oils,
<https://upcommons.upc.edu/bitstreams/e220fde2-2f4b-4196-8fd4-952d037bda95/download>
38. Temperature-dependence of olive oil viscosity - An-Najah Staff,
https://staff-old.najah.edu/sites/default/files/Temperature-Dependence_of_Olive_Oil_Viscosity.pdf

39. A NEW VISCOSITY-TEMPERATURE RELATIONSHIP,
<https://academicjournals.org/journal/JPTAF/article-full-text-pdf/47DA1979161>
40. Modeling The Viscosity of the Vegetable Oils of Argan, Avocado,
[https://www.rjpbcs.com/pdf/2016_7\(6\)/\[221\].pdf](https://www.rjpbcs.com/pdf/2016_7(6)/[221].pdf)
41. Comparative study of the kinematic viscosity versus temperature for,
<https://www.jocpr.com/articles/comparative-study-of-the-kinematic-viscosity-versus-temperature-for-vegetable-oils-argan-avocado-colza-sunflower-and-olive.pdf>
42. Viscosity of Vegetable Oils by Temperature | PDF - Scribd,
<https://www.scribd.com/document/402602652/Visc-Aceites-Veg>
43. The Quality Prediction of Olive and Sunflower Oils Using NIR ... - MDPI,
<https://www.mdpi.com/2304-8158/14/13/2152>
44. The cold pressing of olive oil | Treurer EVOO,
<https://treurer.com/en/cold-pressing-of-olive-oil/>
45. Scourtins Filtres – Artisanat Provençal / La Scourtinerie,
<https://www.scourtinerie.com/en/scourtins-filtres>
46. Read About A Traditional Olive Oil Press Online | La Tienda,
<https://www.tienda.com/learn-about-spain/one-of-the-last-old-style-olive-oil-mills>
47. Sensory Analysis in Olive Oil – Negative Attributes,
<https://olivewellnessinstitute.org/article/sensory-analysis-in-olive-oil-negative-attributes/>
48. Quality assurance of olive oil - SGS INSTITUT FRESENIUS,
<https://sgs-institut-fresenius.de/en/health-nutrition/food-industry/your-products/olive-oil>
49. Olive Oil | Food Safety Authority of Ireland,
<https://www.fsai.ie/enforcement-and-legislation/legislation/food-legislation/olive-oil>
50. New EU regulations on olive oil - Mérieux NutriSciences,
<https://www.merieuxnutrisciences.com/regulation-olive-oil/>
51. Characterization of the Key Odorants Causing the Musty and Fusty,
<https://pubmed.ncbi.nlm.nih.gov/34854681/>
52. INTERNATIONAL OLIVE COUNCIL,
<https://www.internationaloliveoil.org/wp-content/uploads/2022/10/COI-T20-Doc.-15-REV-8-2015-ENG.pdf>
53. Extra Virgin Olive Oil: How to Recognize Quality and Defects,
<https://oliointini.it/en/extra-virgin-olive-oil-how-to-recognize-quality-and-defects/>
54. Sensory Defects of Virgin Olive Oil from a Microbiological Perspective,
https://www.researchgate.net/publication/272959761_Sensory_Defects_of_Virgin_Olive_Oil_from_a_Microbiological_Perspective
55. Common Sensory Defects in Olive Oil Explained,
<https://bhooc.com/blogs/articles/common-sensory-defects-in-olive-oil-explained>
56. Comparative study of virgin olive oil sensory defects,
<https://www.semanticscholar.org/paper/Comparative-study-of-virgin-olive-oil-se>

- [nsory-Morales-Luna/8109ba11d035095c73cd0a95a8b14ad9eec6b5ee](https://doi.org/10.3390/foods10091810)
57. Tradition vs. Innovation: How the Quality of Olive Oil Changes in a, <https://oliointini.it/en/tradition-vs-innovation-how-the-quality-of-olive-oil-change-s-in-a-modern-mill/>
 58. Integral centrifuges for olive oil extraction, at the third millenium, https://www.researchgate.net/publication/43763729_Integral_centrifuges_for_olive_oil_extraction_at_the_third_millenium_threshold_Transformation_yields
 59. Production of pomace olive oil - Digital CSIC, <https://digital.csic.es/bitstream/10261/2464/1/Orujo.pdf>
 60. Agrochemical characterisation of "alperujo", a solid by-product of the, <https://pubmed.ncbi.nlm.nih.gov/14592750/>
 61. Agrochemical characterisation of "Alperujo", a solid by-product of the, https://www.researchgate.net/publication/5381178_Agrochemical_characterisation_of_Alperujo_a_solid_by-product_of_the_two-phase_centrifugation_method_for_olive_oil_extraction
 62. Exact Solution of Terzaghi's Consolidation Equation and Extension, https://file.scirp.org/Html/18-7401369_30767.htm
 63. Terzaghi's Theory of Consolidation - Elementary Engineering, <https://elementaryengineeringlibrary.com/civil-engineering/soil-mechanics/terzaghi-theory-of-consolidation/>
 64. Mathematical Model of Mechanical Oil Expression from Oilseeds, https://www.researchgate.net/publication/229294376_Mathematical_Model_of_Mechanical_Oil_Expression_from_Oilseeds
 65. An Introduction to Poroelasticity - Pure, <https://pure.au.dk/portal/files/116801789/An%20Introduction%20to%20Poroelasticity.pdf>
 66. An introduction to linear poroelasticity - arXiv, <https://arxiv.org/pdf/1607.04274>
 67. EVALUATION OF A MATHEMATICAL MODEL FOR OIL, <https://pdfs.semanticscholar.org/8c79/7f72c5a943fde6c6c1681aba36d1a4fb5100.pdf>
 68. Terzaghi's consolidation theory - GGU Software, <https://www.ggu-software.com/en/glossary/terzaghis-consolidation-theory>
 69. Terzaghi's principle - Wikipedia, https://en.wikipedia.org/wiki/Terzaghi%27s_principle
 70. Coefficient of Consolidation by Inflection Point Method - ResearchGate, https://www.researchgate.net/publication/239388866_Coefficient_of_Consolidation_by_Inflection_Point_Method
 71. Determination of the Coefficient of Consolidation Using the Inflection, https://www.researchgate.net/publication/390620298_Determination_of_the_Coefficient_of_Consolidation_Using_the_Inflection_Point_on_the_Pore_Pressure_Dissipation_Curve
 72. evaluation of a mathematical model for oil extraction from oleaginous, https://www.researchgate.net/publication/269651173_EVALUATION_OF_A_MATHEMATICAL_MODEL_FOR_OIL_EXTRACTION_FROM_OLEAGINOUS_SEEDS
 73. Research on relation between consolidation coefficient and,

https://www.researchgate.net/publication/281306807_Research_on_relation_between_consolidation_coefficient_and_consolidation_stress_of_silt_in_Wenzhou_s_hoal

74. Optimising Dead-End Cake Filtration Using Poroelasticity Theory,
<https://www.mdpi.com/2673-3951/2/1/2>
75. EN 1995-1-1 Timber Checks,
https://download.infograph.de/man_en/en1995_timber_checks.pdf
76. Compression Perpendicular to Grain Guide | SPEC Toolbox,
<https://spectoolbox.com/compression-perpendicular-to-grain/>
77. Compression perpendicular to the grain - ResearchGate,
https://www.researchgate.net/publication/36450283_Compression_perpendicular_to_the_grain
78. Design of timber structures Volume 3 - Swedish Wood,
<https://www.swedishwood.com/siteassets/5-publikationer/pdfer/sw-design-of-timber-structures-vol3-2022.pdf>
79. State-of-the-Art Review of Approaches for the Design of Timber,
<https://ascelibrary.org/doi/10.1061/%28ASCE%29ST.1943-541X.0000838>
80. Define a Beam with a Notch at the Support_5,
https://www.graitec.com/Help/Advance_Design/En/beam-notch-support_5.htm
81. Eurocode 5: Timber Structures Design | PDF | Screw - Scribd,
<https://www.scribd.com/document/708925492/Borrador-Eurocodigo-20XX>