

Advanced Smokehouse Engineering: Thermodynamic Control, Mass Transfer Kinetics, and Bacterial Mitigation in Hot and Cold Smoking

1. Introduction to Multiphase Biochemical Engineering in Food Preservation

The commercial exploitation and preservation of highly perishable protein matrices, notably teleost fish and mammalian muscle, represent a cornerstone of modern biochemical food engineering. In its native physiological state, harvested muscle tissue undergoes a rapid post-mortem deterioration cascade driven by autolytic enzymatic activity, the chemical oxidation of delicate lipids, and the logarithmic proliferation of microbial pathogens¹. To arrest these multiphasic degradation pathways, the application of sodium chloride in conjunction with thermal dehydration and the deposition of wood smoke—collectively known as curing and smoking—has evolved from a rudimentary survival technique into a highly controlled, industrial process¹.

The successful execution of hot and cold smoking modalities requires an intricate equilibrium between osmotic mass transfer, protein solubilization, thermodynamic atmospheric control, and stringent biosecurity measures. This equilibrium is particularly volatile in cold-smoking applications, where the ambient temperature of the smoking chamber must be strictly maintained below 85°F (approximately 29°C)¹. Operating within this mesophilic temperature zone provides absolutely zero thermal lethality to contaminating pathogens; therefore, the toxicological safety of the final product relies entirely on the synergistic hurdle effect established by osmotic dehydration, the bacteriostatic toxicity of deposited phenols, and the aggressive lowering of water activity¹. Conversely, hot smoking relies on highly calibrated thermal shocks to achieve pasteurization, demanding precise mechanical convection to prevent the violent rupture of the epidermal tissue¹.

This exhaustive analysis delineates the physical chemistry, thermodynamic engineering, and microbiological kinetic modeling required to design, construct, and operate state-of-the-art cold and hot smokehouses. It explores the structural requirements of subterranean smoke delivery, the complex psychrometrics of active cooling coils, the Fickian diffusion kinetics of brining, and the advanced predictive models—specifically the Baranyi-Roberts and modified Gompertz equations—utilized to mitigate the catastrophic threat of *Staphylococcus aureus* enterotoxins and *Clostridium botulinum* neurotoxins. Furthermore, this report contextualizes these engineering parameters within the shifting regulatory landscape of the European Union, notably the 2024 prohibition of liquid smoke flavourings and the stringent TA Luft 2021 emissions standards, which collectively force a technological renaissance in traditional

smokehouse design.

2. Structural Engineering and Spatial Configuration of the Smokehouse

The foundational principle of cold smokehouse design is the physical separation of the smoke-generating firebox (pyrolysis chamber) from the curing chamber where the biological product is housed. If the exothermic heat of combustion is permitted to radiate directly into the curing chamber, the ambient temperature will invariably exceed the critical 85°F (29°C) threshold, thereby denaturing the delicate myofibrillar proteins, initiating unwanted thermal coagulation, and dangerously accelerating bacterial growth¹.

2.1 Subterranean Smoke Delivery and Passive Thermal Transfer

To achieve sufficient natural cooling, the pyrolysis chamber must be constructed at a designated distance from the smoking cabinet, utilizing the ambient environment to strip sensible heat from the smoke aerosol before it contacts the food. The optimal geometric distance between the fire pit and the smoker is universally recognized as 4 to 7 feet (1.2 to 2.1 meters)⁴. The two components must be positioned on different elevations, with the curing chamber located significantly higher than the firebox to induce a natural thermodynamic draft, eliminating the strict necessity for mechanical induction fans which can over-aerate the smoldering wood and ignite a secondary flame⁴.

The most thermally efficient mechanism for cooling smoke passively is the utilization of a subterranean delivery pipe or trench. By burying the conduit, the system leverages the massive thermal inertia of the surrounding soil to rapidly absorb heat from the smoke via conduction. A properly engineered subterranean trench should be excavated to a width of 8 inches and a total depth of 11 inches⁴. The trench channel itself occupies the lower 8 inches, leaving 3 inches of vertical space for a protective soil cover, which acts as the primary insulation layer against diurnal temperature fluctuations⁴.

The conduit connecting the fire pit to the chamber should measure 4 to 6 inches (10 to 15 cm) in diameter⁴. Suitable materials for this subterranean pipe include stainless steel, sewer clay pipe, concrete pipe, or copper; plastic PVC must never be utilized due to the immediate risk of toxic off-gassing, halogenated hydrocarbon release, and thermal deformation near the firebox⁴. To facilitate optimal fluid dynamics and ensure the smoke flows freely, the pipe must be installed with a slight upward incline of 5 to 10 degrees, translating to a vertical rise of approximately 1 inch per linear foot⁴. A critical safety gap of at least 1 foot must be maintained between the active firepit and the beginning of any wooden trench coverings to eliminate the possibility of flames reaching combustible materials. This transition zone is typically covered by an 18-inch by 18-inch metal plate or concrete slab⁴. In sandy or geologically unstable soils, the trench walls require reinforcement with gravel or small rocks to prevent structural collapse under the weight of the insulating topsoil⁴.

2.2 Hot Smoking Architecture: The Torrey Kiln Standard

While cold smokehouses rely on separation and passive cooling, commercial hot smokehouses are highly engineered thermal processing vessels designed to forcefully denature proteins and

deliver significant microbial lethality¹. The execution of a commercial hot smoke requires highly precise, sequential temperature ramping to ensure the core of the fish or meat achieves pasteurization temperatures without violently rupturing the exterior musculature. The modern standard utilizes mechanical forced-convection systems, most notably the Torry Kiln design, which dictates strict aerodynamic geometries¹.

The Torry Kiln forces a high-velocity mixture of air and smoke horizontally across the product. To ensure uniform mass and heat transfer, the kiln is equipped with specialized baffles and diffusers that break up laminar airflow, creating turbulent micro-eddies that wrap the smoke around the entire surface area of the fillets⁴. The process progresses through three distinct thermodynamic stages. First, a preliminary desiccation phase is sustained at 30°C for 30 to 60 minutes with maximal smoke output and high volumetric airflow (with the air inlet half to three-quarters open)¹. This phase evaporates superficial moisture and polymerizes the surface proteins. Attempting to apply high heat immediately to wet flesh results in the violent boiling of surface water, which irreversibly shreds the delicate myomeres¹.

Following desiccation, the thermostat is elevated to 50°C and the fresh air intakes are heavily restricted (a quarter open) to dramatically elevate the relative humidity within the chamber¹. Elevated humidity is crucial at this stage to prevent excessive total weight loss (yield reduction). Finally, an aggressive temperature spike to 80°C is executed to achieve thermal lethality, coagulating the remaining actin and sarcoplasmic proteins into an opaque, rigid matrix¹.

3. Commercial Building Codes and Fire Safety Compliance

The physical construction of the smoking cabinet and its associated exhaust systems must adhere to rigorous fire safety and building codes, particularly in commercial or urban settings where the risk of catastrophic conflagration is high. In European jurisdictions, such as Germany, the construction of smokehouses is heavily regulated by local building codes, notably the Berlin Building Code (Bauordnung Berlin, BauO Bln).

According to § 14 of the BauO Bln, all fire installations and exhaust systems (Feuerungsanlagen) must be operationally safe and fire-resistant to prevent the generation and spread of fire and smoke to adjoining structures⁶. When a smokehouse is integrated into a larger commercial facility or shares walls with other processing rooms, the structural barriers separating the smoking unit must meet strict fire resistance ratings based on the designated building class (Gebäudeklasse)⁹.

Building Class (Gebäudeklasse)	Structural Description	Required Ceiling/Wall Fire Rating	Pipe Penetration Seal Rating
Class 1 & 2	Freestanding or small structures, max 7m height, max	F30 (Feuerhemmend / Fire-retardant)	R30

	2 units of 400m ²		
Class 3	Other buildings up to 7m height	F30 (Feuerhemmend / Fire-retardant)	R30
Class 4	Buildings up to 13m height, units max 400m ²	F60 (Hochfeuerhemmend / Highly fire-retardant)	R60
Class 5	Other buildings, including underground structures	F90 (Feuerbeständig / Fire-resistant)	R90

Table 1: Fire Resistance Requirements for Commercial Smokehouse Enclosures (Adapted from BauO Bln)⁹.

For commercial facilities falling under Classes 4 and 5, § 30 of the BauO Bln mandates the use of designated fire walls (Brandwände) to divide large structures into safe fire compartments (Brandabschnitte)⁶. These fire walls must be constructed entirely from non-combustible materials and must remain structurally intact even under additional mechanical stress during a structural fire, requiring a minimum F90 rating⁸.

The integration of smoke delivery pipes and high-velocity exhaust stacks presents a critical vulnerability in these fire compartments. Any penetrations through these F90 ceilings or walls must be meticulously sealed with approved pipe penetration seals (Rohrabschottungen) that match the fire resistance rating of the barrier itself (e.g., an R90 seal for an F90 wall) to prevent vertical or horizontal fire propagation⁹. Furthermore, the building code dictates spatial setback distances (Abstandsflächen) from neighboring property lines. The depth of the clearance area is generally calculated as 0.4 times the height of the wall (0.4 H), with an absolute minimum of 3 meters, ensuring that exhaust fumes and radiant heat do not endanger adjacent urban infrastructure¹¹.

4. Thermodynamic Control and Psychrometric Chilling Mechanisms

While subterranean pipes provide excellent passive cooling during winter months, commercial processing facilities operating year-round in varying climates must employ active thermodynamic controls. The primary objective is to guarantee the curing chamber remains below 85°F (29°C) during cold smoking¹. Operating above this threshold initiates the premature

denaturation of myosin heavy chains and accelerates the logarithmic growth phase of dangerous mesophilic bacteria¹.

The management of the chamber's internal atmosphere requires a deep understanding of psychrometrics—the physical properties of gas-vapor mixtures. Cooling and dehumidifying the hot smoke involves lowering the air temperature below its dew point, forcing water vapor and heavy organic fractions to condense out of the air stream¹⁴. On a psychrometric chart, this process is represented by a line sloping downward and to the left, indicating simultaneous reductions in dry-bulb temperature, wet-bulb temperature, specific humidity, and enthalpy¹⁵.

4.1 Active Heat Exchangers and Cooling Coils

To actively chill the hot smoke generated by the firebox, commercial systems interpose finned-tube heat exchangers, specifically cooling coils, directly into the smoke delivery pathway. A cooling coil removes heat from the passing aerosolized smoke by transferring it to a chilled fluid—typically chilled water (40–45°F) or a direct expansion (DX) refrigerant like R-410A¹⁴.

As the hot smoke passes over the chilled surface of the coil, two simultaneous thermodynamic energy transfers occur. First, sensible cooling takes place, where the dry-bulb temperature of the smoke drops as thermal energy is conducted into the chilled fluid¹⁴. Second, and more importantly for flavor profiling, latent cooling occurs. When the surface temperature of the coil falls below the dew point of the smoke, water vapor condenses out of the aerosol¹⁴. In the context of wood smoke, this condensation effectively acts as a fractional distillation mechanism. The heavy, high-boiling-point tar and creosote compounds condense out of the smoke stream onto the cold metal plates, purifying the smoke and allowing only the desirable, low-temperature volatile phenols (such as guaiacol and syringol) to reach the product².

To engineer a cooling coil capable of maintaining a smokehouse below 85°F (29°C), precise calculations of airflow (Cubic Feet per Minute, CFM) and required cooling capacity (British Thermal Units, BTU) are required. The total cooling capacity of the coil is determined by the

enthalpy difference (Δh) of the entering hot smoke and the leaving chilled smoke. The fundamental thermodynamic equation used by HVAC engineers is:

$$Q_{total} = 4.5 \times CFM \times \Delta h$$

Where Q_{total} is the total heat removed in BTU/hr, 4.5 is a standard conversion constant (derived from the density of standard air and the conversion of minutes to hours), CFM is the volumetric flow rate, and Δh is the change in enthalpy in BTU/lb of dry air¹⁸.

The physical design of the cooling coil must account for the heavy particulate load of wood smoke. Standard HVAC fin spacing may quickly become fouled by creosote¹⁴. Therefore, smokehouse heat exchangers must utilize wider fin spacing (e.g., fewer fins per inch) to handle the dirty environment, and the tubes are often constructed from stainless steel or coated in

epoxy to resist the highly corrosive, acidic nature of the smoke condensate¹⁴. The face velocity of the smoke across the coil must be carefully controlled, typically kept between 2.0 and 2.5 m/s, to ensure adequate residence time for heat transfer without stripping the smoke entirely of its aromatic properties²⁰. If DX coils are utilized, the evaporation temperature should be strictly controlled between 4°C and 7°C to prevent the coil from freezing over due to the high moisture content of the smoke²⁰.

5. Electrostatic Smoke Deposition and Efficiency Kinetics

To maximize commercial throughput and reduce the time the highly perishable product spends in the mesophilic danger zone, modern facilities frequently integrate electrostatic precipitation (ESP) technology into the curing chamber. Electrostatic smoke elimination utilizes electromagnetic forces to rapidly and uniformly drive smoke particles directly into the biological matrix²¹.

In an electrostatic smoking chamber, the incoming smoke particles are passed through high-voltage ionization wires where they acquire a strong negative electrostatic charge²². Simultaneously, the food product acts as a grounded receiver, carrying a relative positive charge. The resulting electrostatic potential gradient—often operating on the order of 160,000 to 500,000 volts per inch—creates an intense attraction that forcefully precipitates the ionized smoke particles directly onto the surface of the meat or fish²⁴.

This technology radically alters the temporal kinetics of cold smoking. Traditional passive cold smoking relies on long exposure times, often extending for several days, for the smoke to slowly settle onto the product via gravity and ambient diffusion²¹. Electrostatic smoking actively depletes the smoke in the chamber, massively accelerating the deposition rate and reducing the necessary curing time to a mere 1.5 to 3 hours²¹. This rapid deposition not only minimizes the time the product is exposed to ambient temperatures but also drastically reduces the overall consumption of wood chips, lowers energy expenditure, and limits the unnecessary yield loss associated with prolonged dehydration²³.

While ESP is highly effective, the accumulation of smoke deposits on the ionizing wires and collection plates leads to a predictable decay in deposition efficiency over time. Freshly cleaned two-stage ESP systems demonstrate an initial removal efficiency of 98% to 99.5% for fine smoke particles as small as 0.1 micrometers²². However, as the heavy, organic tar aerosols load onto the collection plates, they gradually shield the electric field. This shielding effect reduces the ionization potential, leading to a front-loaded, linear decay in efficiency²⁵. Field studies demonstrate that the Clean Air Delivery Rate (CADR) decays at rates of 0.042% to 0.149% per mg/m² of cumulative smoke loading²⁵. Unlike disposable HEPA filters—which suffer permanent and irreversible charge destruction and efficiency collapse when exposed to heavy cigarette or wood smoke due to the degradation of their polymer electret fibers—hard-plate ESP systems can be fully restored to their baseline 97%+ efficiency simply by washing away the tar deposits during routine maintenance cycles²².

Filtration Technology	0.1µm Fine Smoke Removal Rate	Annual Energy Use (10,000 m³/h)	Response to Heavy Smoke Loading
Electrostatic Precipitation (ESP)	98 - 99.5%	1,200 kWh	Gradual decay; fully restored by washing plates
HEPA Filtration	95 - 99%	2,800 kWh	Irreversible charge destruction; requires total replacement
Activated Carbon	70 - 85%	1,500 kWh	Rapid saturation; ineffective for particulate capture

Table 2: Comparison of Smoke Removal and Deposition Technologies²².

6. Osmotic Mass Transfer and Brining Kinetics

Before the teleost or mammalian muscle can be subjected to either the passive or electrostatic smoking phase, it must undergo a rigorous brining protocol. The infusion of sodium chloride into the biological matrix is a highly controlled, multiphase biochemical engineering process designed to achieve osmotic dehydration, structural modification, and absolute biosecurity¹.

6.1 Fickian Diffusion and Muscle Architecture

When a fish fillet is submerged in a hypertonic saline solution, a counter-current mass transfer occurs: sodium and chloride ions diffuse into the sarcoplasm, while intracellular water is osmotically extruded from the tissue into the brine¹. This non-steady-state diffusion of solute through the permeable biological medium is mathematically modeled using Fick's Second Law of Diffusion:

$$\frac{\partial C}{\partial t} = D_{eff} \frac{\partial^2 C}{\partial x^2}$$

Here, C represents the concentration of NaCl in the tissue, t is the brining time, x is the spatial distance from the fillet surface, and D_{eff} is the effective diffusion coefficient¹.

The effective diffusion coefficient (D_{eff}) for NaCl in teleost muscle typically ranges from

$0.47 \times 10^{-10} \text{ m}^2/\text{s}$ to $1.33 \times 10^{-9} \text{ m}^2/\text{s}$ ¹. This aggregate metric is heavily influenced by the complex morphology of the tissue. In pelagic fatty fish, such as Atlantic salmon (*Salmo salar*), lipid contents can exceed 20% to 30%¹. Because lipids are inherently hydrophobic, these dense adipose tissues act as physical barriers that severely obstruct the aqueous diffusion pathways¹. Consequently, lean sections of the fillet absorb salt rapidly, while lipid-dense regions suffer from severe diffusion limitations, creating high spatial heterogeneity in salt concentrations¹. To overcome this resistance, advanced processors may employ kinetic enhancers, such as ultrasonic cavitation, which has been shown to increase the salt D_{eff} by upwards of 402% to 653% by creating microscopic cavitation bubbles that disrupt cellular tortuosity¹.

6.2 The Salometer Paradigm and Target Concentrations

To exert absolute control over these mass transfer kinetics, the specific gravity of the brine must be meticulously calibrated using a Salometer, an instrument standardized specifically for NaCl solutions at 60°F (15.5°C)¹. The scale ranges from 0 degrees (distilled water) to 100 degrees (a fully saturated solution containing exactly 26.395% NaCl by weight)¹. Global processing standards mandate the utilization of brines strictly calibrated between 70 and 80 degrees Salometer (approximately 18.47% to 21.11% NaCl by weight)¹. An 80-degree brine provides a mathematically optimal osmotic gradient, driving salt into the deepest geometric center of the musculature within a commercially viable timeframe, without inducing the catastrophic protein dehydration associated with hyper-saturated brines¹. The residence times within this 80-degree brine are strictly determined by the thickness of the fillet and the ultimate smoking modality.

Fish Cut / Thickness	Cold Smoking Residence Time (80° Brine)	Hot Smoking Residence Time (80° Brine)
Thin Fillets (e.g., Perch, Trout)	5 - 15 minutes	5 - 10 minutes
1/2-inch Fillets	30 minutes	15 minutes
1-inch Fillets	1 hour	30 minutes
1.5-inch Fillets	2 hours	1 hour
Large Whole Fatty Fish (e.g., Herring)	4 - 5 hours	4 hours

Table 3: Optimized Residence Times for 80-Degree Salometer Wet Brining¹.

If processors mistakenly utilize ultra-heavy brines exceeding 90 degrees Salometer, the extreme ionic strength causes the superficial muscle fibers to violently shrink, dehydrate, and form a densified physical barrier—a condition universally known as case hardening¹. This densified barrier traps internal moisture while leaving the core dangerously under-cured, completely compromising the biosecurity of the product. Furthermore, throughout the brining protocol, the ambient temperature of the solution must never exceed 60°F (15.5°C) to prevent the logarithmic proliferation of pathogens and autolytic enzymatic degradation¹.

6.3 Efflorescence Thermodynamics and Pellicle Genesis

The execution of an 80-degree Salometer brining protocol is not merely for flavor; it facilitates two critical surface phenomena: the absolute prevention of efflorescence and the genesis of the protective pellicle.

Efflorescence occurs when the localized ambient relative humidity drops below the Efflorescence Relative Humidity (ERH) of sodium chloride, which exists dynamically between 43% and 47% RH¹. If a fillet is extracted from a supersaturated >90-degree brine and placed in a high-velocity drying kiln, the rapid evaporation of solvent water forces the stagnant boundary layer of liquid on the fish skin into a metastable, supersaturated state¹. Spontaneous heterogeneous nucleation triggers, causing the salt to violently transition back into a solid crystalline lattice, precipitating directly onto the pigmented epidermis as highly visible, chalky white creeping salt structures¹. Restricting primary brines strictly to 80 degrees Salometer and applying a mandatory post-brining hydrostatic cold-water rinse flushes away this high-molarity boundary layer, replacing it with a dilute fluid film that evaporates completely before achieving the critical mass required for nucleation, entirely neutralizing the threat of efflorescence¹. Simultaneously, the high localized ionic strength of the 80-degree brine (significantly exceeding 0.3 M NaCl) acts as a powerful chaotropic agent on the cut surface of the flesh. The chloride ions aggressively intercalate between the endogenous myosin heavy chains, disrupting electrostatic linkages and depolymerizing the functionally insoluble myofibrillar lattice¹. This solubilizes the myosin and actin into a viscous, sticky proteinaceous exudate that is drawn to the surface via osmotic exchange. During the preliminary drying phase of the kiln (typically at 30°C to 38°C), this exudate desiccates, cross-links, and polymerizes into the pellicle—a robust, glossy biopolymer membrane¹. The pellicle serves two profound thermodynamic purposes: it acts as a molecular sponge with a high affinity for binding vapor-phase aromatic phenols, and it serves as a rigid, impermeable physical barrier that strictly prevents the catastrophic exudation of valuable intramuscular lipids during the extreme thermal stress of hot smoking¹.

7. Microbiological Biosecurity: Mesophilic and Psychrotrophic Kinetics

Because cold smoking fundamentally operates below 85°F (29°C), the process itself imparts

absolutely zero thermal lethality¹. The prevention of catastrophic foodborne illness therefore relies entirely on manipulating the chemical microenvironment to suppress the growth kinetics of highly virulent, toxigenic pathogens—specifically *Staphylococcus aureus* and *Clostridium botulinum*.

7.1 Mitigation of *Staphylococcus aureus* and Enterotoxin A

Staphylococcus aureus is a ubiquitous, facultative anaerobic bacterium capable of tolerating exceptionally harsh osmotic conditions, making it a primary threat in cured meats and fish²⁸. A characteristic feature distinguishing *S. aureus* from other pathogens is its high tolerance for

low water activity, possessing the capability to proliferate in environments with an a_w as low as 0.86, and sodium chloride concentrations up to 15% to 20%³⁰.

While the optimum growth temperature for *S. aureus* is approximately 42.0°C, empirical kinetic data demonstrate that its absolute growth range extends from a minimum of 5.9°C to a maximum of 49.2°C²⁹. Consequently, the bacterium remains highly metabolically active within the standard cold-smoking temperature band of 15°C to 29°C. Genomic evidence and in vitro analyses suggest that during colonization or growth in favorable conditions, *S. aureus* replicates rapidly, demonstrating generation (doubling) times between 1 and 3 hours³³. Under strict anaerobic conditions, the growth rate is reduced—with generation times extending to 80 minutes compared to 35 minutes aerobically—but proliferation remains significant²⁸.

The profound danger of *S. aureus* lies in its synthesis of highly potent staphylococcal enterotoxins (SEs), predominantly Staphylococcal Enterotoxin A (SEA)²⁸. SEA is extraordinarily heat-stable and resistant to proteolytic degradation. Thermal inactivation profiles demonstrate that SEA can easily withstand boiling water; achieving total biological denaturation requires exposure to 121°C for 10 to 30 minutes³⁵. Furthermore, studies indicate that partially heat-inactivated SEs can undergo structural renaturation and regain serological toxicity when held at room temperature³⁸. Consequently, if a cold-smoked product is subjected to temperature abuse during processing and SEA is synthesized, any subsequent reheating or cooking by the consumer will be entirely ineffective at neutralizing the toxin or preventing staphylococcal food poisoning³⁵.

To predict and mathematically prevent the proliferation of *S. aureus*, biochemical engineers utilize advanced predictive microbiology, predominantly the modified Gompertz model and the Baranyi-Roberts model⁴⁰. The Baranyi model is particularly effective at simulating the lag, exponential, and stationary phases of bacterial growth by calculating the physiological adjustment of the cells to their environment. The primary Baranyi equation is expressed analytically as:

$$y(t) = y_0 + \mu_{max} A(t) - \ln \left(1 + \frac{e^{\mu_{max} A(t)} - 1}{e^{y_{max} - y_0}} \right)$$

Where $y(t)$ is the logarithmic cell density at time t , y_0 is the initial cell density, y_{max} is the

asymptotic maximum carrying capacity, μ_{max} is the maximum specific growth rate, and $A(t)$ is the adjustment function defining the critical lag phase duration (λ)⁴².

During cold smoking, the engineering objective is to manipulate the secondary environmental parameters to indefinitely prolong the lag phase duration (λ) and suppress the specific growth rate (μ_{max}). By maintaining the ambient temperature strictly below 29°C, dropping the superficial pH via the deposition of organic wood smoke acids, and aggressively lowering the water activity (a_w) below 0.96 through the 80-degree brining protocol, the processor forces the physiological state parameter (h_0) into a highly extended lag phase³¹. This multi-hurdle approach prevents the bacteria from ever transitioning into the exponential growth phase required to synthesize lethal concentrations of SEA²⁸.

7.2 The Psychrotrophic Threat: *Clostridium botulinum* Type E

While *S. aureus* requires mesophilic temperatures to thrive, the marine environment naturally harbors an obligate anaerobe capable of devastating psychrotrophic growth: *Clostridium botulinum* Type E (and non-proteolytic Types B and F)¹. Unlike their terrestrial, proteolytic counterparts, these specific aquatic strains possess the terrifying biological capability to germinate, metabolize, and synthesize lethal botulinum neurotoxin at standard commercial refrigeration temperatures, with an absolute minimum growth threshold as low as 38°F (3.3°C)¹. The threat of botulism is profoundly magnified by modern commercial packaging technologies. To inhibit the growth of aerobic spoilage organisms (such as *Pseudomonas*) and artificially extend the physical shelf life of the smoked product, manufacturers predominantly utilize vacuum-sealed, Reduced Oxygen Packaging (ROP)¹. By intentionally eradicating ambient oxygen, the processor inadvertently engineers the perfect optimal anaerobic microenvironment required for *C. botulinum* spores to germinate¹. Because cold smoking offers absolutely no thermal destruction of these highly heat-resistant spores, the absolute biosecurity of the product relies entirely on achieving a legally mandated chemical metric known as Water Phase Salt (WPS)¹.

WPS mathematically quantifies the actual concentration of sodium chloride residing strictly within the biologically available aqueous portion of the tissue, completely disregarding the inert lipid and solid protein fractions¹. The mathematical formula is defined as:

$$WPS(\%) = \left(\frac{\%NaCl}{\%NaCl + \%Moisture} \right) \times 100$$

To legally and safely package smoked fish in anaerobic environments, global health authorities—specifically the FDA—mandate that the brining protocol must achieve an absolute minimum WPS of 3.5% in the deepest, thickest portion of the loin muscle¹. If the formulation

hits this 3.5% threshold, the extreme osmotic pressure permanently arrests the germination of *C. botulinum* Type E spores, neutralizing the threat of neurotoxigenesis even if the product is subjected to moderate temperature abuse during the logistics chain¹.

8. Thermal Lethality and Pasteurization Kinetics in Hot Smoking

In stark contrast to cold smoking, hot smoking utilizes a destructive thermal process explicitly designed to forcefully denature the proteins, fully cook the flesh, and deliver significant microbial lethality¹. The ambient 80°C environment of the final Torry Kiln stage must be maintained until the deepest geometric core of the tissue registers a temperature sufficient to guarantee the destruction of resilient vegetative pathogens¹.

The efficacy of this thermal lethality step is quantified mathematically using D-values and z-values. The D-value (Decimal Reduction Time) is the time required at a specific, constant temperature to destroy 90% (a 1-log reduction) of a target pathogen population³². The z-value defines the temperature increase required to reduce the D-value by a factor of 10, indicating the pathogen's relative sensitivity to temperature changes⁵⁰.

For the eradication of *Listeria monocytogenes*—a highly resilient, psychrotrophic vegetative pathogen universally targeted in ready-to-eat meats and fish—empirical analyses establish a strict 6D (99.9999% logarithmic reduction) processing requirement⁵⁰. In complex meat matrices, the D-value for *L. monocytogenes* at 70°C is approximately 0.4 minutes⁵⁰. Therefore, to achieve the mandated 6D reduction, the geometric core of the product must be held at 70°C for a minimum of 2.4 minutes⁵⁰.

Target Pathogen	Meat Matrix	D-value at 70°C	Z-value	Required 6D Time at 70°C
<i>Listeria monocytogenes</i>	All Meats	~0.40 min	4.4 - 7.5 °C	2.4 minutes
<i>Salmonella spp.</i>	Poultry / Beef	0.30 - 0.36 min	5.5 °C	1.8 - 2.2 minutes
<i>Escherichia coli</i> O157:H7	Beef / All Meats	0.20 - 0.30 min	~5.0 °C	1.2 - 1.8 minutes

Table 4: Thermal Inactivation Kinetics for Vegetative Pathogens in Meat Matrices⁵⁰. For *Salmonella spp.*, the 6D value at 70°C ranges from 1.8 to 2.2 minutes depending on the specific meat type and fat content⁵⁰. For Shiga toxin-producing *Escherichia coli* (STEC), the 6D requirement is appreciably lower, demanding only 1.2 to 1.8 minutes at 70°C⁵⁰. By driving the

Torry Kiln to an 80°C ambient atmosphere, the processor ensures the geometric core rapidly achieves and significantly surpasses these critical time-temperature parameters, guaranteeing a pasteurized, biosecure product before it enters the chilling and packaging phases¹.

9. Environmental Emissions, PAHs, and Chemical Contaminants

The pyrolysis of hardwood chips to generate smoke invariably produces a highly complex aerosol of volatile organic compounds, particulate matter, and carcinogenic hydrocarbons. Consequently, the commercial operation of smokehouses requires strict regulatory oversight to protect both the consumer from toxicological ingestion and the surrounding environment from atmospheric pollution.

9.1 Strict Emissions Control: The TA Luft 2021 Mandate

In the European Union, specifically Germany, smokehouse atmospheric emissions are rigorously governed by the *Technische Anleitung zur Reinhaltung der Luft* (TA Luft). The 2021 novellation of the TA Luft drastically tightened the acceptable limits for various airborne pollutants emitted by industrial facilities, forcing a massive technological upgrade across the sector⁵⁴.

For commercial smoking installations, several parameters are strictly monitored and enforced. The general emission limit for particulate matter (Gesamtstaub) has been aggressively halved from the previous 2002 standard of 20 mg/m³ down to a stringent 10 mg/m³, requiring the mandatory installation of advanced electrostatic precipitators, wet scrubbers, or baghouse filters on the exhaust stacks⁵⁵. Furthermore, the emission of Total Carbon (Gesamtkohlenstoff)—which represents the aggregate volatile organic compounds (VOCs) generated during wood pyrolysis—is strictly capped at 50 mg/m³⁵⁶.

Crucially, the TA Luft 2021 reclassified formaldehyde, a natural and unavoidable byproduct of wood combustion, due to its proven carcinogenic properties. Under the updated regulations, exhaust emissions of formaldehyde from smokehouses must not exceed a mass concentration of 5 mg/m³ or a total mass flow of 12.5 g/h⁵⁵. Facilities must implement continuous emission monitoring systems and deploy catalytic or thermal oxidizers to remain compliant with these stringent thresholds, failing which operations can be legally suspended⁵⁴.

Pollutant Category	TA Luft 2021 Emission Limit (Concentration)	Mass Flow Threshold
Particulate Matter (Gesamtstaub)	10 mg/m ³ (reduced from 20 mg/m ³)	> 0.40 kg/h
Total Carbon (VOCs)	50 mg/m ³	> 0.50 kg/h
Formaldehyde	5 mg/m ³	> 12.5 g/h

Table 5: Central Emission Limits for Smokehouses under TA Luft 2021⁵⁵.

9.2 Polycyclic Aromatic Hydrocarbons (PAHs)

The primary toxicological concern regarding the direct consumption of smoked foods is the deposition of Polycyclic Aromatic Hydrocarbons (PAHs). PAHs are highly carcinogenic and mutagenic chemical compounds formed naturally during the incomplete combustion and pyrolysis of organic matter⁶⁰. To protect public health, the European Commission, under Regulation (EU) 2023/915, enforces strict maximum limits for PAHs in smoked meats and fish⁶³. The regulatory framework utilizes Benzo[a]pyrene (BaP) as the primary marker for PAH toxicity, alongside the aggregate sum of four specific high-molecular-weight PAHs (PAH4: benzo[a]pyrene, benz[a]anthracene, benzo[b]fluoranthene, and chrysene)⁶⁰. For smoked fish muscle, the maximum allowable limits are exceptionally tight: BaP must not exceed 2.0 µg/kg, and the total PAH4 must remain strictly below 12.0 µg/kg⁶⁰.

Smoked Product Category	Benzo[a]pyrene (BaP) Limit	PAH4 Sum Limit
Smoked Fish & Fishery Products	≤ 2.0 µg/kg	≤ 12.0 µg/kg
Smoked Prawns & Crustaceans	≤ 5.0 µg/kg	≤ 30.0 µg/kg

Table 6: PAH Maximum Limits for Smoked Seafood under EU Regulation 2023/915⁶⁰.

The formation of these carcinogenic compounds is highly temperature-dependent. Empirical studies demonstrate that higher wood pyrolysis temperatures in the smoke generator (e.g., exceeding 400°C to 500°C) drastically increase the yield of high-molecular-weight PAHs while shifting the average aerosol particle diameter from ~600 nm down to ~100 nm⁶¹. Conversely, controlling the smoldering combustion temperature below 300°C significantly reduces the tar content in the condensate and limits PAH formation⁶⁷.

The smoking modality also influences PAH accumulation. Because hot smoking requires sustained elevated ambient temperatures, it generally results in significantly higher PAH concentrations compared to cold smoking. Research indicates a potential 200% increase in the average sum of PAHs in hot-smoked salmon (65°C to 80°C) versus cold-smoked salmon (15°C to 30°C)⁷⁰. The type of wood utilized also plays a vital role; harder woods with higher lignin content alter the combustion profile, with studies indicating that plum and oak wood promote higher PAH levels than beech wood during hot smoking⁶².

9.3 The 2024 EU Flavourings Ban and the Return to Traditional Smoking

To circumvent the PAH risks associated with atmospheric smoke, many commercial processors historically transitioned to the use of "liquid smoke"—purified smoke condensates from which the heavy tars and carcinogenic PAHs had been largely filtered out⁶⁷.

However, in 2024, the European Food Safety Authority (EFSA) fundamentally disrupted the global processing industry by refusing to renew the authorization for eight primary liquid smoke flavouring products⁶⁷. While liquid smoke successfully reduced PAH exposure, the EFSA identified two specific compounds within the condensates—furan-2(5H)-one and benzene-1,2-diol—that demonstrated concerning genotoxic (DNA-damaging) effects *in vivo*⁷². Because the exposure estimates for these compounds exceeded the Threshold of Toxicological Concern (TTC) for DNA-reactive mutagens (0.0025 µg/kg body weight per day), the EU initiated a mandatory phase-out ban, with transitional periods ending between 2026 and 2029 depending on the food category⁷².

Paradoxically, traditional atmospheric smoking methods were not restricted by this ruling, as the legislation (Regulation EC No 2065/2003) strictly governs artificial food additives (flavourings) rather than traditional culinary processing techniques⁶⁷. Consequently, the industry is currently undergoing a massive operational reversion to traditional atmospheric hot and cold smoking⁶⁷. To remain compliant with both the stringent PAH limits of EU 2023/915 and the strict exhaust emission limits of TA Luft 2021, modern processors are now forced to engineer highly sophisticated smoke generators capable of precision low-temperature pyrolysis (sub-300°C), combined with electrostatic deposition to speed up processing, and advanced exhaust scrubbing technologies to capture volatile formaldehyde⁶⁷.

10. Conclusion

The commercial design and operation of hot and cold smokehouses transcend traditional culinary arts, demanding a rigorous application of thermodynamic engineering, mass transfer physics, and microbiological kinetic modeling.

To successfully execute cold smoking, the facility must physically separate the pyrolysis chamber from the curing cabinet, frequently utilizing engineered subterranean trenches and psychrometrically calibrated chilling coils to forcibly maintain the ambient smoke temperature below 85°F (29°C). This low-temperature threshold is an absolute biological necessity; breaching it provides a permissive environment for the rapid physiological adjustment and logarithmic growth of *Staphylococcus aureus*. If allowed to proliferate, this pathogen synthesizes highly heat-stable enterotoxins (such as SEA) against which subsequent consumer thermal treatments are entirely useless. By modeling this behavior via the Baranyi-Roberts and Gompertz equations, engineers can manipulate the microenvironment to permanently extend

the lag phase duration (λ).

Simultaneously, the biological matrix itself must be prepared via aggressive osmotic dehydration. By strictly calibrating brines between 70 and 80 degrees Salometer, the processor optimizes Fickian diffusion, solubilizes myofibrillar proteins to form a protective and adsorptive pellicle, and ensures the deep tissue achieves a Water Phase Salt (WPS) concentration exceeding 3.5%. This precise formulation establishes the critical biochemical hurdle required to permanently arrest the psychrotrophic germination of *Clostridium botulinum* Type E in

anaerobic packaging.

As regulatory bodies continue to aggressively tighten environmental emission standards (TA Luft 2021) and restrict genotoxic liquid smoke additives, the industry must rely heavily on structural and thermodynamic innovation. The integration of advanced heat exchangers, structural fire-wall compliance under the BauO Bln, precise pyrolysis temperature control to minimize PAH formation, and electrostatic precipitation will define the future of biosecure, legally compliant, and organoleptically superior smoked foods.

Works cited

1. 71 Fish Brining and Smoking Protocols.pdf
2. Cold smoking with a transmission oil cooler,
<https://www.bbq-brethren.com/threads/cold-smoking-with-a-transmission-oil-cooler.21255/>
3. Grenz- und Richtwerte zur Beurteilung der Immissionsbelastung,
https://www.stadtklima-stuttgart.de/index.php?luft_grundlagen_grenzwerte
4. Smokehouse Pipe - Meats and Sausages,
<https://www.meatsandsausages.com/smokehouse-plans/smokehouse-pipe>
5. DIY Underground Cold Smoker Build Backyard Smokehouse Project,
<https://www.youtube.com/shorts/b5BS8eYvBWE>
6. Bauordnung für Berlin (BauO Bln) - MFW-Immobilien,
<https://mfw-immobilien.de/wp-content/uploads/2022/09/Bauordnung-fuer-Berlin.pdf>
7. Bauordnung für Berlin (BauO Bln),
http://www.linksfraktion-berlin.de/fileadmin/linksfraktion/Kommunales/Gesetze_und_Verordnungen/BauordnungF00379.pdf
8. § 30 BauO Bln – Brandwände | Gesetze.co, https://gesetze.co/BE/BauO_Bln/30
9. Gebäudeklassen der Berliner Bauordnung Rohrdurchführung durch,
https://tragwerk-und-statik.de/dokument/Bauordnung_Berlin_Geb%C3%A4udetechnik_O_4720.pdf
10. Die Bauordnung für Berlin in der Fassung vom 3 ... - Baurecht.de,
<https://www.baurecht.de/landesbauordnung-Berlin.html>
11. BauO Bln - Bauordnung für Berlin - umwelt-online,
https://www.umwelt-online.de/regelwerk/bau/laender/berlin/bo_ges.htm
12. Brandenburgische Bauordnung (BbgBO) - BRAVORS,
https://bravors.brandenburg.de/gesetze/bbgbo_2016
13. Cold smoking in warm climate : r/Charcuterie - Reddit,
https://www.reddit.com/r/Charcuterie/comments/1qmozc4/cold_smoking_in_warm_climate/
14. Understanding Cooling Coils: Their Role in HVAC, Dehumidification,
<https://www.dehumidifiers.com/post/understanding-cooling-coils>
15. HVAC Air Handling Unit Design Considerations - PDH Online,
<https://pdhonline.com/courses/m250/m250content.pdf>
16. HVAC Made Easy - Overview of Psychrometrics - PDH Online,
<https://pdhonline.com/courses/m135/m135content.pdf>

17. Cooling Coils: HVAC Applications, Specs and Selection Guide,
<https://domirefrigeration.com/cooling-coils/>
18. Coil Capacity Calculator — Cooling & Heating | BTU/hr, kW,
<https://calcengineer.com/hvac/coil-capacity-calculator/>
19. HVAC Formulas and Calculations Field Reference Guide ... - Belimo,
https://www.belimo.com/ca/en_US/blog/hvac-formulas-and-calculations-guide
20. Essential Guide to Choosing Coil Types in Heat Exchangers,
https://www.boyicooling.com/blog/Key-Points-for-Selection-of-Various-Coil-Types-in-Heat-Exchanger_b7664
21. How to reduce the smoking time by 15 times - DonSimon.net,
<https://donsimon.net/en/ds-review/elektro-smoker/>
22. Complete 2026 Guide to Electrostatic Smoke Elimination - Kelv ESP,
https://www.kelv-esp.com/news_details/333.html
23. Smoking with ionization follows different rules - EBSmoke,
<https://www.ebsmoke.com/post/fleischwirtschaft-en>
24. Electrostatic smoking - US3203809A - Google Patents,
<https://patents.google.com/patent/US3203809A/en>
25. A Performance Study of Electrostatic Air Filtration - LakeAir Air Purifiers,
<https://www.lakeair.com/iaq-education/lakeair-research-library/electrostatic-air-filtration/>
26. umsetzung der luftqualitätsrichtlinie ((eu) 2024/2881) in deutsches,
https://www.bundesumweltministerium.de/fileadmin/Daten_BMU/Download_PDF/Glaeserne_Gesetze/21_LP/bimschg_eu_luftqualitaet/Stellungnahmen/Verbaende/bimschg_eu_luftqualitaet_stn_vci_bf.pdf
27. How to Calculate CFM for HVAC (Formulas + Examples),
<https://hvacloadcalculate.com/blog/calculate-cfm-hvac/>
28. Staphylococcus aureus growth and enterotoxin A production in an,
<https://pubmed.ncbi.nlm.nih.gov/11808796/>
29. Growth kinetics of Staphylococcus aureus and background,
<https://pubmed.ncbi.nlm.nih.gov/32981731/>
30. The effect of temperature and water activity on the growth of,
<https://cjfs.agriculturejournals.cz/pdfs/cjf/2009/11/03.pdf>
31. (PDF) The effect of temperature and water activity on the growth of,
https://www.researchgate.net/publication/281609462_The_effect_of_temperature_and_water_activity_on_the_growth_of_Staphylococcus_aureus
32. Determination of Thermal Sensitivity of Staphylococcus aureus,
<https://www.saspublishers.com/article/9226/download/>
33. Rapid cell division of Staphylococcus aureus during colonization of,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC6425579/>
34. The distribution of bacterial doubling times in the wild - PMC - NIH,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC6015860/>
35. [Temperature dependence of staphylococcal enterotoxin ... - PubMed,
<https://pubmed.ncbi.nlm.nih.gov/22894066/>
36. Thermal stability and structural changes in bacterial toxins,
<https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0172445>

37. Chemical/Biological and Decontamination Agent Information,
<https://iwaste.epa.gov/guidance/chemical-biological/agent-info?agent=staphylococcal-enterotoxin>
38. Thermal Inactivation of Staphylococcal Enterotoxins B and C,
<https://journals.asm.org/doi/pdf/10.1128/am.26.6.938-942.1973>
39. (PDF) Thermal Inactivation of Staphylococcal Enterotoxins B and C,
https://www.researchgate.net/publication/18401817_Thermal_Inactivation_of_Staphylococcal_Enterotoxins_B_and_C
40. Growth and Modeling of Staphylococcus aureus in Flour Products,
https://www.researchgate.net/publication/313903618_Growth_and_Modeling_of_Staphylococcus_aureus_in_Flour_Products_under_Isothermal_and_Nonisothermal_Conditions
41. Predictive model of Staphylococcus aureus growth on egg products,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC6484050/>
42. Baranyi-Roberts Microbial Growth Model Calculator,
<https://metricgate.com/docs/baranyi-growth-model/>
43. How to determine microbial lag phase duration? - bioRxiv,
<https://www.biorxiv.org/content/10.1101/2022.11.16.516631v1.full-text>
44. The Baranyi and Roberts Growth Model - Search R-project.org,
https://search.r-project.org/CRAN/refmans/growthrates/html/grow_baranyi.html
45. Staphylococcus aureus Growth Boundaries - PMC,
<https://pmc.ncbi.nlm.nih.gov/articles/PMC123857/>
46. Model of Staphylococcus aureus Growth and Reproduction on the,
<https://www.mdpi.com/2075-5309/15/6/874>
47. Clinical Prevalence, Antibioqram Profiling and Gompertz Growth,
<https://www.mdpi.com/2079-6382/11/9/1270>
48. Fish and Fishery Products Hazards and Controls Guidance - FDA,
<https://www.fda.gov/files/food/published/Fish-and-Fishery-Products-Hazards-and-Controls-Guidance-Chapter-13-Download.pdf>
49. Performance Specification of Time-temperature Integrators,
<http://lib3.dss.go.th/fulltext/Journal/Journal%20of%20food%20science/2003%20v.68/jfsv68n1p0002-0009ms20020169%5B1%5D.pdf>
50. Standardising D and Z values for cooking raw meat,
<https://www.mpi.govt.nz/dmsdocument/44044/direct>
51. A Practical Guide to Sous Vide Cooking - Douglas Baldwin,
<https://douglasbaldwin.com/sous-vide.html>
52. Standardizing D and Z Values for Cooking Raw Meat: A Final Report,
<https://policycommons.net/artifacts/12583744/standardising-d-and-z-values-for-cooking-raw-meat/13485174/>
53. (PDF) D- and Z- values for Listeria monocytogenes and Salmonella,
https://www.researchgate.net/publication/6169335_D-_and_Z-_values_for_Listeria_monocytogenes_and_Salmonella_Typhimurium_in_packaged_low-fat_turkey_bologna_subjected_to_a_surface_pasteurization_treatment
54. Die neue TA Luft – Grenzwerte & Änderungen - TÜV Nord,
<https://www.tuev-nord.de/de/wissen/wissen-kompakt/die-neue-ta-luft-2021/>

55. TA Luft: Vorschriften, Grenzwerte und betroffene Anlagen im Überblick,
<https://www.forum-verlag.com/fachwissen/energie-und-umwelt/ta-luft/>
56. TA Luft 2021: Unsere Erkenntnisse zu strengeren Grenzwerten,
<https://www.desotec.com/de/knowledge-hub/article/ta-luft-2021-our-insights-on-stricter-air-emission-limits-and-wider-remit-in-germany>
57. Bestandsfassung TA Luft von 2021 Entwurfsfassung 2025 - IHK,
<https://www.ihk.de/blueprint/servlet/resource/blob/6521396/de3b7c6e7baf8f5e607e62fad1010f75/zusammenfassende-synopse-ta-luft-data.pdf>
58. Novellierung der TA Luft mit strengeren Grenzwerten und ... - neutralox,
<https://www.neutralox.com/de/newsreader/novellierung-der-ta-luft.html>
59. TA Luft Grenzwerte: Übersichtstabelle für Betreiber - NEWFOOX,
<https://newfoox.com/ta-luft-grenzwerte-tabelle/>
60. (PDF) PAHs in Smoked Fish and Seafood: Compliance with UK Limits,
https://www.researchgate.net/publication/407548515_PAHs_in_Smoked_Fish_and_Seafood_Compliance_with_UK_Limits
61. (PDF) Effects of Smoking Temperature, Smoking Time, and Type of,
https://www.researchgate.net/publication/343517068_Effects_of_Smoking_Temperature_Smoking_Time_and_Type_of_Wood_Sawdust_on_Polycyclic_Aromatic_Hydrocarbon_Accumulation_Levels_in_Directly_Smoked_Pork_Sausages
62. Influence of Fish Species and Wood Type on Polycyclic Aromatic,
<https://www.mdpi.com/2304-8158/13/12/1790>
63. Polycyclic Aromatic Hydrocarbons - Galab Laboratories GmbH,
<https://www.galab.com/polycyclic-aromatic-hydrocarbons/>
64. Maximum levels for certain contaminants in food - EUR-Lex,
<https://eur-lex.europa.eu/EN/legal-content/summary/maximum-levels-for-certain-contaminants-in-food.html>
65. Commission Regulation (EU) 2023/915 - EUR-Lex - European Union,
<https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=CELEX:32023R0915>
66. PAH in Smoked Spices: EU 2023/915 | CardamomNepal,
<https://cardamomnepal.com/guides/pah-in-smoked-spices-eu>
67. Traditional smoking not affected by the ban - Eurofish,
<https://eurofish.dk/traditional-smoking-not-affected-by-the-ban/>
68. Characterization of Smoke Emissions from Wood and Plastic,
<https://dr.lib.iastate.edu/bitstreams/11cb022b-5b7b-4a2a-af14-51780cf921ac/download>
69. Characterization of the Aroma Profile of Food Smoke at Controllable,
<https://www.mdpi.com/2297-8739/10/3/176>
70. Effects of smoke flavoring using different wood chips and,
<https://journals.plos.org/plosone/article/file?type=printable&id=10.1371/journal.pone.0227508>
71. Influence of smoking parameters on the concentration of polycyclic,
https://www.researchgate.net/publication/45273044_Influence_of_smoking_parameters_on_the_concentration_of_polycyclic_aromatic_hydrocarbons_PAHs_in_Danish_smoked_fish
72. Traditional Smoking vs Liquid Smoke: What the EU Decision Reveals,

- <https://www.salamandersauce.com/salamander-hot-sauce-blog/traditional-smoking-vs-liquid-smoke>
73. Smoke Flavourings | Food Safety Authority of Ireland,
<https://www.fsai.ie/enforcement-and-legislation/legislation/food-legislation/flavourings/smoke-flavourings>
 74. New EU regulation for smoke flavouring primary products,
<https://europe.novataste.com/en/magazines/Authorisation-of-smoke-flavourings>
 75. Ban on smoke flavourings: new EU regulations,
<https://www.eurofins.com/en-nl/food-feed-testing/knowledge-news-articles/alert-ban-on-smoke-flavourings/>
 76. Commission Implementing Decision (EU) 2024/2066 of 31 July,
https://eur-lex.europa.eu/legal-content/EN/TXT/PDF/?uri=OJ:L_202402066
 77. Smoke Flavours - News | Bell Flavors & Fragrances EMEA,
<https://www.bell-europe.com/en/smoke-flavours/>
 78. Smoke flavourings | EFSA - European Union,
<https://www.efsa.europa.eu/en/topics/topic/smoke-flavourings>
 79. Smoke flavouring renewals - existing - Food Safety,
https://food.ec.europa.eu/food-safety/food-improvement-agents/flavourings/smoke-flavouring-renewals-existing_en
 80. The Influence of the Smoking Process on the Physical Parameters of,
<https://www.mdpi.com/2076-3417/15/11/6098>